

Three-axle rear tipper semitrailer design: steel body with chute and platform



S.KI 24 Model: S.KI 7.2 SL 06 SR


Technical specifications

Semitrailer height loaded – min. recommended	1,190 mm
Semitrailer height loaded - Semitrailer horizontal.	1,170 mm
Semitrailer height loaded max. permissible 1,270 mm	
Semitrailer height empty & coupled - Semitrailer horiz.	1,200 mm
Semitrailer height empty & coupled - max. permissible	1,300 mm
Front overhang radius (front beam)	1,385 - 1,410 mm
Front overhang radius with platform	1,635 mm
Pivoting radius as per ISO 1726	2,300 mm
Tyres for driving height = 470 (overall height)	385 / 65 R 22,5"
Tyres for driving height = 470 (overall height + 30 mm)	425 / 65 R 22,5"
Axle spread	1,210 / 1,310 mm
Wheelbase	4,900 / 4,800 mm
Rear overhang chute	2,615 / 2,715 mm
Rear overhang supported hinged tailgate	2,590 / 2,690 mm
Rear overhang combi-door vertical	2,675 / 2,775 mm
Middle of heating funnel to King Pin	150 mm
Middle of heating funnel to middle of longitudinal axis	1,065 mm
Body height	1,660 / 1,460 mm
Overall height	3,130 / 2,930 mm
Overall height with roller tarpaulin (+ 100 mm)	3,240 / 3,040 mm
Overall height with sliding tarpaulin (+ 400 mm)	3,530 / 3,330 mm
Loading length with chute	7,300 mm
Loading length with supported hinged tailgate	7,480 mm
Loading length with combi-door vertical	7,690 / 7,660 mm


Technical specifications

Front overhang of '600' canopy	1,205 / 1,145 mm
Front overhang without platform	855 mm
Front overhang with platform	1,360 mm
Overall length with chute (with platform)	8,875 mm
Overall length with combi-door vertical (with platform)	8,935 mm
Ov. length with supported hinged tailgate (with platform)	8,850 mm
Overall length with chute (without platform)	8,370 mm
Ov. length with combi-door vertical (without platform)	8,430 mm
Ov. length with supp. hinged tailgate (without platform)	8,345 mm
Overall length with chute (with '600' canopy)	8,660 mm
Ov. length with combi-door vertical (with '600' canopy)	8,720 mm
Ov. length with supp. hinged tailgate (with '600' canopy)	8,635 mm

Combi-door vertical



Supported hinged tailgate



Additional fittings

All dimensions and weights are approximate. The data relate to a vehicle with base fittings without taking into consideration possible additional fittings. Issued: 20.08.2008

just more.

Trailer

Services

Technology