100% SMART ex works

The TrailerConnect® telematics system is on board every S.CS FREEPOST curtainsider semi-trailer.

All S.CS FREEPOST curtainsiders are equipped with TrailerConnect® telematics as standard. You have immediate access to the Schmitz Cargobull telematics portal and apps beSmart and beUpToDate.

The benefits are:

- Efficient fleet management with real-time information on the actual state of the fleet for your planning.
- Intelligent dispatching that optimises tours and on-time delivery while avoiding empty runs.
- Increased trailer availability proactive maintenance minimises downtime and breakdown.
- Reduction of process costs for trailer utilisation and staff deployment.







(!) EBS (ABS) (i) 137 - - -







S.CS FREEPOST Curtainsider Semi-Trailer

Certified according to DIN EN 12642 Code XL, pillarless design especially for UK and Ireland

The advantages at a glance:

- Rolled, galvanised MODULOS chassis easy to maintain, with high corrosion protection and 10-year guarantee against rusting through
- Schmitz Cargobull aluminium roof with steel outer beam for lateral loading heights of up to 3,200 mm
- Flexible load securing: Continuous lashing holes and optionally 16 pairs of lashing rings 4t
- Free side loading without sliding posts





- 100% SMART Telematics TrailerConnect® CTU is standard ex works. Hardware and basic service can be used immediately
- DIN EN 12642 Code XL certified
- Effective theft protection thanks to standard curtain with steel wire-reinforced belts
- Tried and tested ROTOS axle unit with disc brakes for increased safety and low overall costs




Rolled, galvanised MODULOS chassis - robust, durable and retains its value with low total cost of ownership. Particularly easy to maintain due to bolted and screwed connections. and with a 10-year warranty against rust-through. Hot-dip galvanising offers excellent corrosion protection as well as unmixedrecycling.



ROTOS axles with disc brakes for high road safety and lower total cost of ownership. Six-year warranty on hub and tube.

Schmitz Cargobull aluminium roof



Aluminium roof with galvanised steel outer rail and various load securing options for a lateral loading height of up to 3,200 mm.



Fully certified structure according to DIN EN 12642 Code XL. High security of the goods through integrated theft protection in the curtain.

Structural stiffness certified according to DIN EN 12642 Code XL

S.CS FREEPOST

Pillarless for easy side loading





TrailerConnect® Telematics System CTU control unit, activation and basic contract included ex works**



Rolled, galvanised MODULOS chassis

ROTOS chassis: 1 million km warranty



The right body height for every transport application: available in heights of 4,200 mm, 4,400 mm, 4,600 mm and 4,800 mm.



To facilitate unloading, the curtain can be tensioned from both the front and the rear.



For more safety - underride protection according to ECE regulation 58.03. The forces to be absorbed have almost doubled to 18t.




Load securing straps with lashing eyes on the outside or inside centre on both sides prevent the load from slipping.



of the light and brake connections thanks to a connection bar that can be pulled out to the side, simplifying and speeding up handling.



Flexible load securing with continuous lashing holes in the side and optional 16 pairs of 4 t lashing rings.



LED lights* with lower risk of failure

Schmitz Cargobull Susi-Rail* - Safe operation



The curtain tensioner and the door lock are easy and safe to operate and increase the safety of the driver in everyday life.