



S.KI SOLID | S.KI 36 AT HD 9.6 SR

4-axle rear tipper semi-trailer with rounded steel body

Weights			technically	
Gross weight	GG	kg	54,000	
Aggregate load	AL	kg	36,000	
semi-trailer weight	SL	kg	18,000	
Driving height	FH	mm	470	
Tyres			385/65 R 22,5"	
Measurements			loaded	unloaded
semi-trailer height - min. recommendation to max. permissible	S	mm	1,310- 1,420	1,340- 1,450
semi-trailer height - semi-trailer horizontal	S	mm	1,320	1,180
Axle distance				1310
Wheelbase	R	mm		6,145
Rear overhang with body	N	mm		3,350
Body height				1660
Load volume with chute	V	m ³		35.4
Overall height unloaded horizontal without tarpaulin	HA	mm		3,300
Overall height unloaded horizontal with rollup tarpaulin	HA	mm		3,410
Overall height unloaded horizontal with sliding tarpaulin	HA	mm		3,700
Overall height unloaded tipped without tarpaulin	HK	mm		9,280
Overall height unloaded tipped with rollup tarpaulin	HK	mm		9,380
Overall height unloaded tipped with sliding tarpaulin	HK	mm		9,575
Pivoting radius front only body	F	mm		1,440
Pivoting radius front with rollup tarpaulin and plattform	F	mm		1,620
Pivoting radius front with sliding tarpaulin	F	mm		1,810
Pivoting radius rear as par ISO 1726 without spare wheel	G	mm		2,650
Pivoting radius rear as par ISO 1726 with spare wheel	G	mm		2,650
Internal length surface-mounted body	L	mm		9,500
Front overhang only body	E	mm		900
Front overhang with rollup tarpaulin and plattform	E	mm		1,300
Max. tipping angle		degrees		44
Overall height from fifth wheel to body floor	C	mm		290
Overall length	LA	mm		E+R+N