



Technisches Datenblatt / TECHNICAL DATA SHEET

date

Reifengröße / TIRE SIZE	: 385/65R22.5	max. Tragfähigkeit pro Achse / MAX LOAD PER AXLE	: 9000 kg
Profilbezeichnung / TREAD DESIGN	: RR905	Reifengewicht / TIRE WEIGHT	: 73.2 kg
Tragfähigkeit / LOAD INDEX	: 160	Freigabe-Nr. / APPROVAL NUMBER ECE-R54	: 27021
Geschw.-Kennz. / SPEED INDEX	: K	Freigabe-Nr. / APPROVAL NUMBER ECE-R117-02	: 027288 S2WR2
stat. Halbmesser / STATIC LOAD RADIUS	: 495 mm	Herstellungsland / MANUFACTURING COUNTRY	Thailand
Abrollumfang / ROLLING CIRCUMFERENCE	: 3260 mm		
Außendurchmesser / TIRE OUTER DIAMETER	: 1070 mm	Markierungen / MARKING	
Reifenbreite / TIRE WIDTH	: 380 mm	M+S	YES
Basis Luftdruck / INFLATION PRESSURE	: 9 bar	3PMSF 	YES
Profiltiefe / TREAD DEPTH	: 16.0 mm	Rollwiderstandsbeiwert / ROLLING RESISTANCE LEVEL	5.96N/KN
max. Geschwindigkeit / MAX SPEED	: 110 km/h	CONNECTIVITY 	NO
empfohlene Felge / RECOMMENDED RIM	: 22.5 x 11.75		

empfohlene Verwendung / APPLICATION RECOMMENDATION

Langstrecke / LONG HAUL	<u>Regional / REGIONAL</u>	Baustelle / OFF-ROAD	
Sommer / SUMMER	<u>Ganzjahr / ALL SEASONS</u>	Winter / WINTER	
<u>Lenkachse / STEERING AXLE</u>	Antriebsachse / DRIVE AXLE	<u>Nachlaufachse / SELF STEERING AXLE</u>	<u>Anhänger / TRAILER</u>

Driven The World Over

DOUBLE COIN

All Steel Radial Tyres
385/65R22.5-20PR
RR905
160K

For Europe EAN


8 859513 000012
Export Only (First Quality)



