



Three-axle rear semitrailer with sliding floor

S.SF SLIDING FLOOR

S.SF Sliding Floor

Aggregate load technically possible		27,000 kg
Permitted full weight		35,000 / 39,000 kg
Empty weight +/-3%		7,700 kg
max. permissible payload		27,400 / 31,400 kg
Overall length		14,000 mm
Overall width		2,550 mm
Overall height	HA	4,000 mm
Internal loading length		13,532 mm
Internal loading width	B	2,470 mm
Clear height front		2,660 mm
Clear height rear		2,820 mm
Loading volume:		approx. 92 m ³
Wheelbase	R	7,700 mm
Front axle spacing	W	1,310 mm
Rear axle spacing	W	1,310 mm
Front section dimensions		1,590 mm
Distance between kingpin and semitrailer landing gear		2,420 mm
Fifth wheel height, unloaded with 385/65 R 22.5 tyres	SH	1,150 mm
Fifth wheel height, loaded with 385/65 R 22.5 tyres	SH	1,110 mm
Rear loading height, unloaded, with 385/65 R 22.5 tyres		1,180 mm
Rear loading height, loaded, with 385/65 R 22.5 tyres		1,140 mm

All dimensions and weights are approximate. The data relate to a vehicle with base fittings without taking into consideration possible additional fittings.
Issued: March 2011.

Trailer

Services

Technology

just more.