



S.KI 24 / 10.5 SL06 AK  
Three-axle rear tipper semitrailer with aluminium box-body

**SKI LIGHT**

## S.KI LIGHT Large Volume

Semitrailer height loaded – minimum recommended		1,170 mm
Semitrailer height loaded – semitrailer horizontal	S	1,150 mm
Semitrailer height loaded max. permissible		1,290 mm
Semitrailer height empty & coupled – semitrailer horizontal		1,180 mm
Semitrailer height empty & coupled max. permissible		1,320 mm
Front overhang radius (front beam)		1,425-1,545 mm
Front overhang radius with platform		1,645-1,935 mm
Pivoting radius as per ISO 1726		2,300 mm
Tyres for driving height = 470 (overall height)		385/65 R 22,5"
Tyres for driving height = 470 (overall height +30 mm)		425/65 R 22,5"
Wheelbase	R	7,350 mm
Rear overhang combi-door vertical	N	2,885 mm
Rear overhang supported hinged tailgate		2,865 mm
Rear overhang hinged door		2,980 mm
Centre of heating funnel to King Pin	X	155 mm
Centre of heating funnel to centre of longitudinal axis	Y	995 mm
Body height	H	2,300 / 2,100 / 1,900 / 1,650 mm
Overall height	HA	3,855 / 3,655 / 3,455 / 3,205 mm
Overall height with rollup tarpaulin (+110 mm)		3,965 / 3,765 / 3,565 / 3,315 mm
Loading length of combi-door vertical	L	10,575 / 10,540 / 10,500 / 10,460 mm
Loading length of supported hinged tailgate		10,575 / 10,540 / 10,500 / 10,460 mm
Loading length of hinged door		10,575 / 10,540 / 10,500 / 10,460 mm
Front overhang without platform		1,050 / 970 / 900 / 870 mm
Front overhang with platform		1,515 / 1,515 / 1,360 / 1,260 mm
Overall length with combi-door vertical (with platform)	LA	12,090 / 12,055 / 11,860 / 11,720 mm
Overall length with supported hinged tailgate (with platform)		12,090 / 12,055 / 11,860 / 11,720 mm
Overall length with hinged-door vertical (with platform)		12,090 / 12,055 / 11,860 / 11,720 mm
Overall length with combi-door vertical (without platform)		9,525 / 9,570 / 9,600 / 9,590 mm
Overall length with supported hinged tailgate (without platform)		9,525 / 9,570 / 9,600 / 9,590 mm
Overall length with hinged door vertical (without platform)		9,525 / 9,570 / 9,600 / 9,590 mm

All dimensions and weights are approximate. The data relate to a vehicle with base fittings without taking into consideration possible additional fittings.  
Issued: March 2011.

Trailer

Services

Technology

just more.