



S.KI 24 / 10.5 SL06 SR
Three-axle rear tipper semitrailer with rounded steel body



S.KI SOLID Large Volume

Semitrailer height loaded – minimum recommended		1,200 mm
Semitrailer height loaded – semitrailer horizontal (1,010)	S	1,200 mm
Semitrailer height loaded max. permissible		1,240 mm
Semitrailer height loaded max. permissible (1,040)		1,230 mm
Semitrailer height empty & coupled – max. permissible		1,270 mm
Front overhang radius (front beam)		1,425-1,510 mm
Front overhang radius with platform		1,780 mm
Pivoting radius as per ISO 1726		2,300 mm
Tyres for driving height = 470 (overall height)		385/65 R 22,5"
Tyres for driving height = 470 (overall height +30 mm)		425/65 R 22,5"
Wheelbase	R	7,350 mm
Rear overhang door vertical	N	2,990 mm
Centre of heating funnel to King Pin	X	155 mm
Centre of heating funnel to centre of longitudinal axis	Y	1,065 mm
Body height	H	2,300 / 2,000 mm
Overall height	HA	3,800 / 3,500 mm
Overall height with rollup tarpaulin (+ 110 mm)		3,910 / 3,610 mm
Loading length of door vertical	L	10,545 / 10,500 mm
Front overhang without platform		865 mm
Front overhang with platform		1,525 mm
Overall length with door vertical (without platform)		11,205 mm
Overall length with door vertical (with platform)		11,865 mm

All dimensions and weights are approximate. The data relate to a vehicle with base fittings without taking into consideration possible additional fittings.
Issued: March 2011.

Trailer

Services

Technology

just more.